

ORDER FORM

ORDER e: roofsales@ultraframe.co.uk

QUOTE e: quotes@ultraframe.co.uk

New Build Replacement Project

PLAN VIEW

ACCOUNT No.

Company Name

Order Number

JOB REFERENCE

Company Contact

Telephone No.

Email

Delivery Address

.....

.....

POSTCODE

Delivery Date Req

Quotation Ref

CRITICAL INFORMATION

***Required for structural snow / wind loading**

*Site Postcode

Roof pitch Fixed at 25°

FRONT ELEVATION

CUSTOMER NOTE: Please carefully read the Ultrasky Roof installation guide before filling in order details.

HOW TO PLACE AN ORDER FOR ULTRASKY ROOF:

1. Sketch plan & elevations.
(If necessary, attach photos of existing property. Indicate on drawings if any part of project is existing).
2. Mark and caption the positions of all walls, brick piers, windows/doors, cut outs / intrusions.
3. Mark the preferred positions of any
a) roof windows
or b) rectangular glazed panels.
4. Upon placement of your Ultrasky Roof order, an order confirmation is generated which must be signed and emailed back.

LEFT ELEVATION

RIGHT ELEVATION

Job No.:3598

Please sign and return to
roofsales@ultraframe.co.uk

SIGNED

DATE

ORDER FORM

JOB REFERENCE

ROOF / SITE INFORMATION

Frame Width

ROOF COLOUR

White

Matt Grey

Bespoke RAL/BS Colour

External

Internal

INTERNAL PELMET

Minimum Width (300mm)

Other (300-1200mm) Please state (mm):.....

ROOF / INFORMATION

On Fascia*

Below Fascia

If fitting to a bungalow please indicate Soffit Depth.....

Full Height Walls

Please state on drawing / style and dimensions.

N.B. If order is retro fit then option of on fascia is the only option available.

TOP CAPPINGS

Dome (PVCu)

Aluminium

TIE BARS

White Tie Strut

CONSERVAFLASH

Soaker Only

Yes

BAR UNDERCLADDINGS

Standard (PVCu)

Aluminium

CORNICE

Style 1 Tier

2 Tier

3 Tier

Curved

Colour White

Matt Grey

Deeplas

RAL/BS Colour

EAVES BEAM

Standard (VAAAH)

Structural (SEB)

If using SEB please indicate span and location of doors on drawing.

ROTABOND SEALANT - MS POLYMER

White (NCGS001W)

Black (NCGS001B)

No. Tubes Req:

N.B. For use with Conservaglass

ROOF VENTS AND MECHANISM (mark plan)

PVCu Internal Cladding

Aluminium Internal Cladding

Brass Manual Spindle Manual Spindle and pole Manual Spindle and telescopic pole

Chrome Manual Spindle Manual Spindle and pole

Electric motor with digital thermostat and rain sensor Electric motor and rocker switch

Electric motor with radio and remote control Electric motor with thermostat (AVTD002)

Electric without switch/thermostat (Motor only)

GLASS OPTIONS - WARM EDGE SPACER

Conservaglass

Ultra86 Blue

Ultimate Blue

Blue 4S

Neutral 4S

Aqua 4S

Bronze 4S

Std Blue

Std Neutral

Std Aqua

Std Bronze

Celsius

Celsius One

Celsius Elite

Celsius Clear

ANCILLARY EXTRAS

Job No.:3598

Please sign and return to

roofsales@ultraframe.co.uk

SIGNED

DATE